Project Name: Completing the Required Construction Works for Permit No. 1-2-1873 (Turnout), 1-2-1873 A (Grading and Landscaping) and 1-2-XO 190 (Cross-over).

M/S 45-AL-001-MU-053 A, Milepost 318.38 Rt, Madison County

## Work Description (Please See the Attached Plan Sheet):

- 1. This project will be paid on a Lump sum basis.
- 2. Approximately 1100.00 Sq. Yd.
- 3. Placing the thermoplastic traffic stripping and marking for the right deceleration lane.
- 4. Removing the existing cross-over and reconstruct a new cross-over 95 ft to the south at milepost 318.38 to be aligned with the entrance of the Bristol Creek Subdivision.

2216222

143 1657

120-010659

5. Constructing a 550 ft long left deceleration lane and placing the associating thermoplastic traffic marking and stripping.

## The construction (based on ALDOT 2008 Standard Specifications for Highway Construction) shall include the following items:

600-A-000 - Mobilization (Lump sum)

210-A-000 - Unclassified Excavation

210-D-000 - Borrow Excavation

230-A-000 - Road Bed Processing, 6 inches Minimum

- 301-B Crushed Aggregate Base Course, Plant Mix, 6 inches Compacted Thickness, and Compacted 100% Standard Proctor.
- 401-A-000 Bituminous Treatment "A", (Prime Coat)
- 424-B-681 Superpave Bituminous Concrete Lower Binder Layer, 1 inch Maximum Aggregate Size Mix, ESAL Range C/D (250 lb/yd²)
- 424-B-651 Superpave Bituminous Concrete Upper Binder Layer, 1 inch Maximum Aggregate Size Mix, ESAL Range C/D (250 lb/yd²)
- 424-A-360 Superpave Bituminous Concrete Wearing Surface Layer, 1/2 inch Maximum Aggregate Size Mix, ESAL Range C/D (135 lb/yd²)
- 650-A-000 Top Soil (Approximately 4 inches thick)
- 658-A-000 Hydro Seeding & Mulching (Acre)
- 665-J-000 Silt Fence (L.F.)
- 701-G-000 Solid and Broken Color, Traffic Stripe (L.F.)
  - 1120.50 L.F. of 5 inches thick solid white thermoplastic traffic stripe.
  - 550.50 L.F. of 5 inches thick solid yellow thermoplastic traffic stripe.
  - 470 L.F. of 5 inches thick dotted white thermoplastic traffic stripe, 2 ft long @ 4 ft spacing.
- 703-A Traffic Control Markings (S.F.) White Thermoplastic:
  - 4 Turn Arrows:
    - 2 Right Turn Arrows for the Right Deceleration Lane
    - 2 Left Turn Arrows for the Left Deceleration Lane
- 703-B- Traffic Control Legends (S.F.), White Thermoplastic: 4 of "ONLY", 2 for each turn lane.